

## SONLOK® Thread Sealants

PRODUCT SONLOK	Item Number	Packing	Application	Color	Sp. Gravity	Seal to operating pressure	Viscosity, cps	Temperature Range °F
3511	351150 351125 351100	50 ml 250 ml 10 liter	Ideal for coarse threads, medium strength	White	1.09	Seals operating pressure to 10,000 psi	24,000 / 80,000 Thixotropic	-65 to 300
3540	354050 354025 354000	50 ml 250 ml 10 liter	Cup and Core Plug Sealant	Blue	1.08	Seals operating pressure to 10,000 psi	7,000 / 12,000	-65 to 300
3542	354210 354250 354225 354201 354200	10 ml 50 ml 250 ml 1 liter 10 liter	Ideal for fine threads	Brown	1.06	Seals operating pressure to 10,000 psi	525 / 1,850 Thixotropic	-65 to 300
3545	354510 354550 354525 354501 354500	10 ml 50 ml 250 ml 1 liter 10 liter	No Fillers, Pneumatic hydraulic sealant	Purple	1.20	Seals operating pressures to 10,000 psi	9,000 / 20,000	-65 to 300
3554	355410 355450 355425 355401 355400	10 ml 50 ml 250 ml 1 liter 10 liter	High shear strength, refrigerant sealant	Red	1.02	Seals operating pressures to 10,000 psi	1,500 / 3,500	-65 to 300
3564	356450 356425 356400	50 ml 250 ml 10 liter	General purpose	White	1.17	Seals operating pressures to 10,000 psi	49,500 / 132,000	-65 to 300
3565	356550 356525 356500	50 ml 250 ml 10 liter	General purpose with controlled strength	White	1.10	Seals operating pressures to 10,000 psi	175,000 / 375,000	-65 to 300
3567	356750 356725 356700	50 ml 250 ml 10 liter	Ideal for stainless steel fittings	White	1.14	Seals operating pressures to 10,000 psi	280,000 / 575,000	-65 to 400
3569	356910 356950 356925 356901 356900	10 ml 50 ml 250 ml 1 liter 10 liter	Recommended hydraulic sealant	Brown	1.05	Seals operating pressures to 10,000 psi	300 / 500	-65 to 300
3571	357150 357125 357101 357100	50 ml 250 ml 1 liter 10 liter	High solvent and chemical resistance	Brown	1.10	Seals operating pressures to 10,000 psi	1,000 / 3,000	-65 to 300
3572	357250 357225 357200	50 ml 250 ml 10 liter	Slow cure speed, low strength sealant	White	1.25	Seals operating pressures to 10,000 psi	17,000 / 50,000	-65 to 300
3577	357750 357725 357700	50 ml 250 ml 10 liter	Ideal for coarse threads, medium strength	Yellow	1.09	Seals operating pressures to 10,000 psi	24,000 / 80,000 Thixotropic	-65 to 300
3580	358050 358000	50 ml 10 liter	Low sulfur, low halogen thread sealant	White	1.08	Seals operating pressures to 10,000 psi	300,000 / 800,000	-65 to 400
3592	359250 359225 359200	50 ml 250 ml 10 liter	Medium strength sealant	White	1.21	Seals operating pressures to 10,000 psi	200,000 / 500,000	-65 to 400

**PARSON ADHESIVES, INC.**

3345, Auburn Road, Suite 107, Rochester Hills, MI 48309, USA

tel: 248-299-5585 • fax: (248) 299-3846 • email: sales@parsonadhesives.com • www.parsonadhesives.com